



SCALE 1:50




KENGURU PRO

"KENGURU PRO" LTD

Address: Lauteres street 4, Riga, Latvia, LV-1002
 VAT Reg. No. 40103750152
 Bank: A/S Luminor bank, SWIFT: RIKOLV2X ,
 Bank Account: LV65RIKO0002930161161
 e-mail: info@kengurupro.eu
 www.kengurupro.eu

K-002_kids

Two level monkey bar



The structure consists of six vertical columns and two horizontal monkey bars of different heights. Length of the horizontal monkey bar – 1952 mm, width – 800 mm, distance between each crossbar is 274 mm. The structure is secured together with aluminium clamps.

Installation instructions:

- Choose a suitable underground for the unit (see page 2, table 2)!
- Prepare the construction pit with a drilling machine or other devices.
- Before pouring the concrete all structures elements must be leveled and fixed.
- Complex elements must be fixed and bolted together with metal clamps.
- Ready-made C25 concrete should be used.
- Crossbars installation height can be changed according to customer's wishes.
- Approximately 0,15m³ concrete is needed for each spot foundation.
- Under the structures we recommend to install absorbing rubber cover.

The size of the hole for the foundation is depending on the consistency of the ground. The dimensions mentioned above are applicable for normal conditions with firm ground. If the ground is extremely soft, a much bigger foundation is needed. Use only appropriate material and follow the installation instructions closely!!!

Foundation plan and area of movement of the K-002_kids				Technical information		
Foundation when using Shock absorbing underground (synthetic – rubber granulates)		Beveling of foundation when using loose filling material		width:	1016 mm	
				height:	2050 mm	
				length:	3944 mm	
				largest part:	2650 mm	
				weight:	210,00 kg	
				floor space required	7094 x 4316 mm	
				pipe measurements:	diameter:	wall thickness:
					108 mm	3.2 mm
					33.7mm	3.2 mm
				metal parts:	steel, galvanized, powder coated RAL 7016 (anthracite grey)	
				metal clamps:	siluminium, powder coated, RAL 4010 (Telemagenta)	
				bolts for metal clamps	stainless steel, Pin Hex Button Head Security bolts M10	
				max. free fall height:	< 1683 mm	EN1176-1 annex I table I.1
				user age:	3-14 years	
				certificates:	TÜV Rheinland InterCert Kft.	

